

## Torrens LP




### Standard equipment:

- 3.700.0036 Gun M22 - 3/8"



- 3.701.0015 Lance M22 high/low pressure



- 3.103.0050 Nozzle type 045 (mod. 1211 LP)
- 3.103.0052 Nozzle type 055 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)



- 4.618.0012 High pressure hose 10 m



- Power cable 5 m

### Optional:

**VERSION**  
**60**  
**Hz**  
**AVAILABLE**  
**DETAILS PAGE 33**

**T.S.** Total Stop

### Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection.
- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- Suction and delivery S/S valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge.
- Auxiliary motor for burner.
- By-pass thermal protection with safety valve.
- Integrated detergent suction with external suction probe.
- Pressure regulator.
- Glycerine pressure gauge.
- Panel with analogic controls.
- Accessory holder.
- Power cable holder.
- Heavy duty steel frame.

	Torrens 1211 LP	Torrens 1515 LP	Torrens 2015 LP
code	8.627.0001C	8.627.0002C	8.627.0003C
operat. pressure/max	110/150 bar-11450/2175 psi	150 bar-2175 psi	200 bar-2900 psi
delivery rate	660 l/h-2.91 GPM	900 l/h-3.96 GPM	900 l/h-3.96 GPM
abs. power/voltage	3000W - 230V~50Hz 1ph	5500W - 400V~50Hz 3 ph	7300W - 400V~50Hz 3 ph
motorpump type/RPM	MP3/1450 RPM	MP3/1450 RPM	MP3/1450 RPM
max. temp. inlet/outlet	40/140 °C	40/140 °C	40/140 °C